

**Characteristics :**

Gyproc® Matrix Wall angle is fixed to the perimeter of the wall at the ceiling level to hold the Main T's and give a finish when it terminates on the wall.

Compliance Standards:

IS 513 : Raw material of Metal frames
 IS 16162 : Coil thickness tolerance
 IS 277 : Metal frames coating
 IS 14246 : Prepainted Galvanized Steel

Physical Properties :

Width	: 24±1 mm
Height	: 24±1 mm
Length	: 3000 ±1 mm
Cross Section Area	: 21.57 mm ²
Moment of Inertia _{Ixx}	: 1480.82 mm ⁴
Moment of Inertia _{Iyy}	: 1480.82 mm ⁴
Body	: 0.40 mm thick PPGL with 90GSM Zinc coating
Surface	: Top coat_25 microns & Back coat_10 micron
Colors Available	: White & Black

Saint Gobain India Pvt Ltd - Gyproc® Business reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

Corporate Office: Saint-Gobain India Pvt Ltd, Gyproc Business, Leela Business Park,
 5th Level, Opposite Leela Hotel, Andheri-Kurla Road,
 Andheri (East), Mumbai- 400059, Maharashtra, India

Contact Us : 18001037897 (TOLL FREE)
Email : gyprocindia@saint-gobain.com
Website : https://www.gyproc.in/

